

SWIFT



360° ALUMINIUM BLOCK

Features

- Made of lightweight, corrosion-resistant aluminum for easy handling and durability
- Fully enclosed body with sealed gears and brake for enhanced internal protection
- 360° patented rotating hand chain guide enables operation from any angle
- Galvanized load chain and smooth-finish cover bolts for hygiene and user comfort
- Available in compact sizes with load capacities from 0.25T to 5T and low net weights

Advantages

- Reduces operator fatigue with lighter hoist weight while maintaining strength
- Protects internal mechanisms from dust and contaminants, extending hoist life
- Ensures safe and convenient use in tight or elevated spaces without repositioning
- Suitable for clean environments like medical and food-grade industries
- Offers flexibility for broader usage due to wider hook diameter and compact dimensions

Benefits

- Enhances worker efficiency and safety through easier portability and use
- Minimizes downtime and maintenance costs due to long-lasting components
- Improves ergonomics and safety by allowing remote operation from any direction
- Delivers reliable performance in sensitive workspaces requiring high cleanliness
- Simplifies logistics and reduces freight cost with lower weight per unit



CHAIN PULLEY BLOCK



Safety First

SWIFT



- Constructed of canvas material for durability.
- Convenient belt loop for easy tool belt attachment.
- Velcro flap for quick access.
- Lightweight for user comfort.
- Portable bag is optional for 0.5T model.

Capacity	Tons	0.25	0.5	1	1	1.5	2	2	3	5
Standard Lift	m	2.5	2.5	3	3	3	3	3	3	3
Running Test Load	KN	3.15	6.3	12.5	12.5	20	25	25	40	63
Effort Required to Lift Rated Load	N	260	210	220	350	400	360	370	440	450
No fo Falls		1	1	2	1	1	2	1	2	2
Specification of Load Chain	mm	3.2*9	4.3*12	4.3*12	5.6*15.7	7.1*19.9	5.6*15.7	8*24	7.1*19.9	9*27
Dimensions (mm)	A	89.5	103	103	107	130	107	138.5	130	163
	B	84	102	102	125	148	125	161	148	185
	C	19	24	28	28	30	30	30	36	45
	H	240	270	350	320	367	400	380	447	590
Net Weight	kg	2.5	2.5	7.3	7.2	12.2	11	14.6	17.6	33.2
Extra Weight per Meter of Lifting Height	kg	0.46	0.46	1.26	1.1	1.56	1.8	1.82	2.69	4.4

CONSOLIDATED SWIFT INDUSTRIES LIMITED - A Bajaj Group Company

(Carrying Forward the SWIFT Brand from Consolidated Hoists Private Limited)



+91 94038 92303



enquire@csil.in



www.consolidatedswift.com

Office No. 402 & 403, Akshay Center, 4th Floor, Tilak Road, Shukrawar Peth, Pune - 411002.

