

# SWIFT



## HEAVYMATE



### Features

- Rated capacity of 2.5T for efficient handling of heavy pallets
- Lowered fork height of 65 mm ensures smooth entry beneath low-clearance pallets
- Durable rear and front wheels offer reliable mobility
- Multiple fork outside distance options for varied pallet sizes

### Advantages

- High load capacity minimizes trips and boosts productivity in material movement
- Low fork height makes it compatible with a wide range of pallets and containers
- Wheel dimensions ensure better load distribution and smooth movement across surfaces
- Flexible fork spacing allows the handling of different pallet types with a single unit

### Benefits

- Improves efficiency in warehouses and shops with fewer handling cycles required
- Easy to maneuver and operate, even in space-constrained areas
- Reduces operator fatigue due to smoother rolling and better handling ergonomics
- One-time investment for multi-pallet handling, saving on cost and space

HAND PALLET TRUCK



**Safety First**



Nylon wheel  
Welding pump



PU wheel  
Casting pump

Item	Unit	Specification
Rated Capacity	kg	2500
Lowered Fork Height	mm	65
The Rear Wheel	mm	160*50
The Front Wheel	mm	63*100
Maximum Height of Fork	mm	175
The Overall Height	mm	1155
The Overall Length	mm	1516
Fork Length	mm	1150
Fork Outside Distance	mm	460/520/550/685
Fork Outside Distance	mm	14.5
Pallet Fork Size	mm	150*50
Net Weight	kg	60-65

## CONSOLIDATED SWIFT INDUSTRIES LIMITED - A Bajaj Group Company

(Carrying Forward the SWIFT Brand from Consolidated Hoists Private Limited)



+91 94038 92303



enquire@csil.in



www.consolidatedswift.com

Office No. 402 & 403, Akshay Center, 4th Floor, Tilak Road, Shukrawar Peth,  
Pune - 411002.

